

02-09-02

A

PATENT

Attorney Docket No. DEEPF64.001C1

Date: February 8, 2000

Page 1

02/08/00



jci760 U.S. PTO ASSISTANT COMMISSIONER FOR PATENTS

WASHINGTON, D.C. 20231

ATTENTION: BOX PATENT APPLICATION

Sir:

Transmitted herewith for filing is a Continuation in Part for patent application 08/739,179.

Inventor(s): **Peen-Pau Cheng**For: **PHOTIC IMAGE PROCESSING DEVICE**

Enclosed are:

- (X) A Specification in 17 pages.
- (X) Two sheet(s) of drawing.
- (X) Assignment and Assignment Recordation Sheet.
- (X) A Check for \$40.00 for Assignment Recordation.
- (X) Initial signed declaration by inventor(s).
- (X) A Supplemental Oath.
- (X) Return prepaid postcard.



CLAIMS AS FILED

FOR	NUMBER FILED	NUMBER EXTRA	RATE	FEE
Basic Fee			\$690	\$690
Total Claims	14 - 20	0 ×	\$18	\$0
Independent Claims	3 - 3 =	0 ×	\$78	\$0
If application contains any multiple dependent claims(s), then add			\$260	\$0
TOTAL FILING FEE				\$690.00

- (X) A check in the amount of \$690.00 to cover the filing fee is enclosed.
- (X) The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Account No. 11-1410. A duplicate copy of this sheet is enclosed.
- (X) Please use Customer No. 20,995 for the correspondence address.

Lowell Anderson
 Lowell Anderson
 Registration No. 30,990
 Attorney of Record

H:\DOCS\LOA\LOA-3604.DOC
 010700

KNOBBE, MARTENS, OLSON & BEAR

A LIMITED LIABILITY PARTNERSHIP INCLUDING
PROFESSIONAL CORPORATIONS

PATENT, TRADEMARK AND COPYRIGHT CAUSES

620 NEWPORT CENTER DRIVE

SIXTEENTH FLOOR

NEWPORT BEACH, CALIFORNIA 92660-8016

(949) 760-0404

FAX (949) 760-9502

INTERNET WWW.KMOB.COM

LOUIS J. KNOBBE*
DON W. MARTENS*
GORDON H. OLSON*
JAMES B. BEAR
DARRELL L. OLSON*
WILLIAM B. BUNKER
WILLIAM H. NIEMAN
LOWELL ANDERSON
ARTHUR S. ROSE
JAMES F. LESNIAK
NED A. ISRAELSEN
DREW S. HAMILTON
JERRY T. SEWELL
JOHN B. SGANGA, JR.
EDWARD A. SCHLATTER
GERARD VON HOFFMANN
JOSEPH R. RE
CATHERINE J. HOLLAND
JOHN M. CARSON
KAREN VOGEL WEIL
ANDREW H. SIMPSON
JEFFREY L. VAN HOOSEAR
DANIEL E. ALTMAN
MARGUERITE L. GUNN
STEPHEN C. JENSEN
VITO A. CANUSO III
WILLIAM H. SHREVE
LYNDIA J. ZADRA-SYMEST
STEVEN J. NATAUPSKY
PAUL A. STEWART
JOSEPH F. JENNINGS
CRAIG S. SUMMERS
ANNEMARIE KAISER

BRENTON R. BABCOCK
THOMAS F. SMEGAL, JR.
MICHAEL H. TRENHOLM
DIANE M. REED
JONATHAN A. BARNEY
RONALD J. SCHOENBAUM
JOHN R. KING
FREDERICK S. BERRETTA
NANCY WAYS VENSKO
JOHN P. GIEZENTANNER
ADEEL S. AKHTAR
GINGER R. DREGER
THOMAS R. ARNO
DAVID N. WEISS
DANIEL HART, PH.D.
DOUGLAS G. MUEHLHAUSER
LORI LEE YAMATO
MICHAEL K. FRIEDLAND
STEPHEN M. LOBBIN
ROBERT F. GAZDZINSKI
STACEY R. HALPERN
DALE C. HUNT, PH.D.
LEE W. HENDERSON, PH.D.
DEBORAH S. SHEPHERD
RICHARD E. CAMPBELL
MARK M. ABUMERI
JON W. GURKA
ERIC M. NELSON
ALEXANDER C. CHEN
MARK R. BENEDICT, PH.D.
PAUL N. CONOVER
ROBERT J. ROBY
SABING H. LEE

KAROLINE A. DELANEY
JOHN W. HOLCOMB
JAMES J. MULLEN, III, PH.D.
JOSEPH S. CIANFRANI
JOSEPH M. REISMAN, PH.D.
WILLIAM R. ZIMMERMAN
GLEN L. NUTTALL
ERIC S. FURMAN, PH.D.
DO TE KIM
TIRZAH ABE LOWE
GEOFFREY Y. HIDA
ALEXANDER S. FRANCO
SANJIVPAL S. GILL
SUSAN M. MOSS
JAMES W. HILL, M.D.
ROSE M. THIESSEN, PH.D.
MICHAEL L. FULLER
MICHAEL A. GUILIANA
MARK J. KERTZ
RABINDER N. NARULA
BRUCE S. ITCHKAWITZ, PH.D.
PETER M. MIDGLEY
THOMAS S. MCCLENAHAN
MICHAEL S. OKAMOTO
JOHN M. GROVER
MALLARY K. MCCARTHY
IRFAN A. LATEEF
AMY C. CHRISTENSEN
SHARON S. NG
MARK J. GALLAGHER, PH.D.
DAVID G. JANKOWSKI, PH.D.
BRIAN C. HORNE
PAYSON J. LEMEILLEUR

OF COUNSEL
JERRY R. SEILERJAPANESE PATENT ATTY
KATSUHIRO ARAI**EUROPEAN PATENT ATTY
MARTIN HELLEBRANDTKOREAN PATENT ATTY
MINCHEOL KIMSCIENTISTS & ENGINEERS
(NON-LAWYERS)

RAIMOND J. SALENIEKS**
NEIL S. BARTFELD, PH.D.**
DANIEL E. JOHNSON, PH.D.**
JEFFERY KOEPKE, PH.D.
KHURRAM RAHMAN, PH.D.
JENNIFER A. HAYNES, PH.D.
BRENDAN P. O'NEILL, PH.D.
THOMAS Y. NAGATA
ALAN C. GORDON
PABLO S. HUERTA
LINDA H. LIU
MICHAEL J. HOLIHAN
YASHWANT VAISHNAV, PH.D.
MEGUMI TANAKA

* A PROFESSIONAL CORPORATION
† ALSO BARRISTER AT LAW (U.K.)
** U.S. PATENT AGENT

Assistant Commissioner for Patents
Washington, D.C. 20231

CERTIFICATE OF MAILING BY "EXPRESS MAIL"

Attorney Docket No. : DEEPF64.001C1
Applicant(s) : Peen-Pau Cheng
For : PHOTIC IMAGE PROCESSING METHOD
Attorney : Lowell Anderson
"Express Mail"
Mailing Label No. : EL017644999US
Date of Deposit : February 8, 2000

I hereby certify that the accompanying

Transmittal in Duplicate; Specification in 17 pages; 2 sheets of drawings;
SIGNED Supplemental Oath by Inventor in 2 pages; **SIGNED** Declaration and
Power of Attorney in 2 pages; Recordation Form Cover Sheet and Assignment in
2 pages; Check(s) for Filing Fee(s); Return Prepaid Postcard

are being deposited with the United States Postal Service "Express Mail Post Office to
Addressee" service under 37 CFR 1.10 on the date indicated above and are addressed to the
Assistant Commissioner for Patents, Washington, D.C. 20231.


Donald King

H:\DOCS\LOA\LOA-3932.DOC
020800

201 CALIFORNIA STREET
SUITE 1150
SAN FRANCISCO, CALIFORNIA 94111
(415) 954-4114
FAX (415) 954-4111

501 WEST BROADWAY
SUITE 1400
SAN DIEGO, CALIFORNIA 92101
(619) 235-8550
FAX (619) 235-0176

3801 UNIVERSITY AVENUE
SUITE 710
RIVERSIDE, CALIFORNIA 92501
(909) 781-9231
FAX (909) 781-4507

1875 CENTURY PARK EAST
SUITE 600
LOS ANGELES, CALIFORNIA 90067
(310) 407-5484
FAX (310) 407-5485

PHOTIC IMAGE PROCESSING METHOD

FIELD OF THE INVENTION

The present invention is a CIP application of the parent application
"Photic Image Processing Device" bearing the serial NO. 08/739,179
5 and filed on October 30, 1996.

The present invention relates to a photic image processing method
that can produce a photic image having high resolution and quality.

BACKGROUND OF THE INVENTION

In general, a photic image processing device at least includes three
10 portions:

- (1) a photic image pick-up component;
- (2) a photic image processing component; and
- (3) an electric power supplier and a motor driver.

As in the prior art, a programmable gain amplifier (PGA) disposed
15 in the photic image processing component is employed for compensating
a non-uniformity appearing among a lamp's brightness, a charge coupled
device (CCD) and a lens.

However, the shortcoming of this compensation by utilizing a PGA
is that, only one single color of the processed photic image is
20 compensated at a time. Hence, if plural colors are required for
processing, accordingly, plural PGAs are demanded. Consequently, the
cost is increased and the electric circuit thereof is therefore becoming
more complicated.

Besides, as disclosed in the prior art, plural exposure periods are
25 utilized for compensating, however, each exposure period can merely
process only one single color correspondingly. Hence, the processing
time required for processing the photic image is accordingly increased.

In addition, when plural PGAs are employed for compensating the photic image, plural analog/digital amplifying devices are correspondingly required. Furthermore, owing to the high price of the analog/digital amplifying device, therefore, total cost of the photic image processing device is enormously increased.

SUMMARY OF THE INVENTION

The major object of the present invention is to provide a photic image processing method which is capable of processing a photic image in a manner of high quality and high resolution.

The photic image processing method of the present invention includes steps of (1) processing a photic image unit to generate a photic image signal having a plurality of basic image signals each of which represents a fundamental color, (2) performing a first regulating compensation to each of the basic image signals of the photic image to generate first compensated basic image signals, (3) multiplexing the first compensated basic image signals in a period of time to generate a multiplexed photic image signal having the compensated basic image signals in series in the period of time, wherein the period is equal to a time of processing a photic image unit, and (4) performing a second regulating compensation for the multiplexed photic image signal to generate a second compensated multiplexed photic image signal.

According to the present invention, the step (1) further includes steps of (1a) generating a light signal to an object for obtaining a reflective signal and (1b) executing a photoelectric conversion in response to the reflective signal for obtaining the photic image signal having the plurality of basic image signals.

In accordance with the present invention, the step (1) further includes a step of (1c) executing a current amplification for the photic image signal in order to enhance an anti-disturbance ability of the photic image signal.

5 According to the present invention, the step (2) further includes steps of (2a) eliminating a common-mode voltage of the photic image signal; (2b) regulating a DC voltage offset of the photic image signal; (2c) amplifying and outputting the photic image signal whose the DC voltage offset is regulated; and (2d) performing the first regulating
10 compensation in response to a control signal, in order to equilibrate the basic image signals of the photic image signal.

In accordance with the present invention, the basic image signals of the photic image signal are respectively 3 basic signals indicative of red, green and blue fundamental colors, and the step (1) is executed by a
15 photic image pick-up circuit including a lamp having a brightness, a lens and charge coupled device (CCD).

According to the present invention, the first regulating compensation regulates and equilibrates the photic image signals of red, green and blue fundamental colors and compensates a lamp aging phenomenon of the
20 photic image pick-up circuit. In addition, the second regulating compensation correlates and compensates a non-uniformity among the lamp's brightness, the lens, and the charge coupled device (CCD).

In accordance with the present invention, the step (3) further includes steps of (3a) equally dividing the period of time into three
25 segments, and multiplexing the 3 basic signals of red, green and blue fundamental colors in the three segments to obtain a multiplexed photic image signal alternately containing therein the 3 basic signals, (3b)

outputting three compensation values at the three segments, each of the three compensation values compensating one of the 3 basic signals of red, green and blue fundamental colors at the corresponding segment in the multiplexed photic image signal, and (3c) compensating the 3 basic
5 signals of red, green and blue fundamental colors in the multiplexed photic image signal by multiplying respectively the three compensation values therefor to accomplish the second regulating compensation.

According to the present invention, the method further includes steps of (5) converting the second compensated multiplexed photic
10 image signal into a digital photic image signal, and (6) generating the control signal corresponding to the digital photic image signal.

The present invention may best be understood through the following description with reference to the accompanying drawings, in which:

BRIEF DESCRIPTION OF THE DRAWINGS

15 Fig. 1 is a system block diagram showing a preferred embodiment of an operation process according to the present invention.

Fig. 2 is a time sequence diagram showing a preferred embodiment of an operation for processing and compensating the R, G and B fundamental - colors of a photic image signal during a period of processing a specific
20 photic image unit according to the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Please refer to Fig. 1, which is a system block diagram showing a preferred embodiment of an operation process according to the present invention showing a photic image processing device 1 and a peripheral
25 interface device 2. The photic image processing device 1 includes: a photic image pick-up circuit 11, a voltage regulating and compensating circuit 12, a multiprogrammable gain amplifying circuit 13, an

analog/digital converting circuit 14, a memory interface control circuit 15, an electric power driving circuit 16 and a driving motor 17.

The photic image picking up circuit 11 further includes: a DC/AC voltage inverting circuit 111, an illumination unit 112 (preferably a lamp), a focusing device 113 (preferably a mirror and a lens), a charge coupled device (CCD) 114 and a preamplifying device 115.

The voltage regulating and compensating circuit 12 includes: a correlated-double sampler 121, a voltage regulator 122, a signal amplifier 123 and an automatic gain controller 124. The multiprogrammable gain amplifying circuit 13 includes: a multiplexer 131, a programmable gain compensator 132 and a multiplier 133.

The memory interface control circuit 15 includes: a control signal operation generator 151, a system memory (system RAM) 152, a peripheral interface controller 153, a microprocessor 154, a programmable memory (EPROM) 155, a Gamma transforming device 156 and a buffer memory (buffer RAM) 157. While the electric power driving circuit 16 includes: a power supplier 161 and a motor driver 162.

The operation process of the photic image processing device according to the present invention is described as follows:

At first, the DC/AC voltage inverting circuit 111 inverts a DC voltage signal into an AC voltage signal having a high frequency and a relatively higher voltage according to an ON/OFF control signal generated and outputted from the control signal operation generator 151, in order to control the illumination unit 112, and accordingly the illumination unit 112 is able to generate and project a light signal on an object, e.g. text or picture (not shown in Fig. 1) in response to the AC voltage signal, consequently, a reflective signal generated by the

reflection of the text and/or the pictures, is further reflected to the focusing device 113, and therefore the focusing device 113 focuses and reflects the reflective signal thereon to the charge coupled device 114 for performing a photoelectric converting operation therefor in order to
5 output a photic image input signal.

Wherein, the charge coupled device (CCD) generates a photic image input signal including the photic image signals of red, green and blue fundamental colors by employing a converting means of phase vs. voltage, in response respectively to a first control signal S1 generated by
10 the control signal operation generator 151 and the focused reflective signal reflected from the focusing device 113. Thereafter, the photic image input signal is transmitted to the preamplifying device 115 from the charge coupled device 114, and the photic image input signal is processed by utilizing a current amplification in order to enhance an anti-
15 disturbance ability of the photic image input signal. However, if the object irradiated by the illumination unit 112 is a transparent object, then merely a relevant equipment for handling the same is needed to equip the object for processing.

Moreover, the correlated-double sampler (CDS) 121 electrically
20 connected to the preamplifying device 115, is used to reduce a common-mode voltage of the photic image input signal, thereafter, the DC voltage offset of the photic image input signal is eliminated by the voltage regulator 122 in which an adder can be included before amplified via the signal amplifier 123; wherein a differential value signal indicated by
25 OFFSET in Fig. 1 cooperates with the voltage regulator 122 during the processing for regulating the DC offset of the photic image input signal.

An automatic gain controller 124 electrically connected to the signal amplifier 123 is used to regulate the equilibrium among the red (R), green (G) and blue (B) fundamental colors of the photic image input signal in response to a control second signal S2 generated and outputted
5 from the control signal operation generator 151, in order to compensate the photic image aliasing caused by the aging phenomenon of the lamp 112.

Please now refer to the multiprogrammable gain amplifying circuit 13, in which the multiplexer 131 electrically connected to the voltage
10 regulating and compensating circuit 12 is used to input the photic image input signal and divide a period of processing a specific photic image unit into three segments in response to a third control signal S3 generated and outputted from the control signal operation generator 151. The period of processing a specific photic image unit is the period for
15 CCD 114 processing a pixel. The multiplexer 131 equally dividing the period of processing a specific photic image unit into three segments, and multiplexing the 3 series of the photic image signals of red, green and blue fundamental colors in each segment of the period to obtain a photic image output signal alternately containing therein the 3 series of
20 photic image signals in order to compensate and correlate a non-uniformity among the brightness of the lamp 112, the lens 113 and the CCD 114. Furthermore, the programmable gain compensator 132 is able to output the compensation values respectively for the R, G and B fundamental colors during each of the three segments of the period for
25 processing the photic image unit in accordance with the third control signal S3. Accordingly, the fundamental colors of R, G and B are respectively compensated by the compensation values and mixed up one

another before outputted by a manner of in a series of photic image signals. Therefore, the compensated fundamental colors of R, G and B respectively outputted from these three segments are transmitted to the multiplier 133 and multiplied respectively to each other.

5 Thereafter, the outputted series of photic image signals are transmitted to the analog/digital converting circuit 14, accordingly the series of photic image signals are converted into a digital photic image signal therein in response to a VRT and a VBR signals.

10 The control signal operation generator 151 generates and outputs the first, second and third control signals S1, S2 and S3 according to the inputted digital photic image signal outputted from the analog/digital converting circuit 14, and the first, second and third control signals S1, S2 and S3 are utilized to execute an operation for generating a photic image output signal. The system memory 152 is used to record and
15 store a correlating curve for the R, G and B fundamental colors. As to the peripheral interface controller 153, e.g. a SCSI peripheral interface controller, it is used to output the photic image output signal to a specified peripheral interface device 2, e.g. a personal computer, in response to a peripheral interface control signal I generated from the
20 control signal operation generator 151. The microprocessor 154 is used to control a process operated in the photic image processing device 1 beginning from picking up a photic image and ending with outputting the photic image output signal via the peripheral interface controller 153. Moreover, the programmable memory 155 is employed to provide a
25 required signal information for the microprocessor 154 during operation. The Gamma transforming device having a Gamma transforming table is used to perform a Gamma transformation in order that the user can

define a color of a photic image by himself for achieving a demanded color. The buffer memory 157 provides the Gamma transforming device 156 with a storing function for storing a photic image information during the execution of the Gamma transformation, and outputs the photic image information outputted from the peripheral interface controller 153 to a specified peripheral interface device 2.

The power supplier 161, e.g. a switch type power supplier is used to provide a power source signal for the photic image device 1, and the motor driver 162 is utilized to drive the driving motor 17. Of course, if the power supplier 161 is able to be combined with the motor driver 162 into a single unit, the power loss induced by the circuit impedance will be accordingly reduced.

In order to further realize the compensating process for the R, G and B fundamental colors executed by the programmable gain compensator 132 of the multiprogrammable gain compensator 13, please refer to Figs. 1 & 2. Fig. 2 is a time sequence diagram showing a preferred embodiment of an operation for processing and compensating the R, G and B fundamental colors in a period of processing a specific photic image unit according to the present invention. In Fig. 2, the multiplexer 131 outputting the R, G and B fundamental colors respectively in three distinct time segments of the period of processing the specific photic image unit by the multiswitching control in response to the third control signal S3. Accordingly, the programmable gain compensator 132 outputs respectively the latching signals and the compensation values RC, GC and BC for the R, G and B fundamental colors at the different time t1, t2 and t3 during compensation.

To sum up, the present invention merely needs a multiplexer 131, a control signal operation generator 151 for controlling the multiplexer 131 and an analog/digital converting circuit 14, to accomplish the same function obtained by utilizing plural multiplexers and plural
5 analog/digital converting circuits as disclosed in the prior art. Hence, the circuit configuration disclosed in the present invention is capable of obtaining a photic image signal having a high resolution and quality but preventing from an evidently cost increment. Therefore, the present invention is a valuable industrial application.

10 While the invention has been described in terms of what are presently considered to be the most practical and preferred embodiments, it is to be understood that the invention need not be limited to the disclosed embodiment. On the contrary, it is intended to cover various modifications and similar arrangements included within the spirit and
15 scope of the appended claims which are to be accorded with the broadest interpretation so as to encompass all such modifications and similar structures.

WHAT IS CLAIMED IS:

1. A photic image processing method comprising steps of:

(1) processing a photic image unit to generate a photic image signal having a plurality of basic image signals each of which represents a
5 fundamental color;

(2) performing a first regulating compensation to each of said basic image signals of said photic image to generate first compensated basic image signals;

(3) multiplexing said first compensated basic image signals in a
10 period of time to generate a multiplexed photic image signal having said compensated basic image signals in series in said period of time, wherein said period is equal to a time of processing a photic image unit ; and

(4) performing a second regulating compensation for said multiplexed photic image signal to generate a second compensated
15 multiplexed photic image signal.

2. A photic image processing method as claimed in Claim 1, where further includes steps of:

(1a) generating a light signal to an object for obtaining a reflective signal; and

(1b) executing a photoelectric conversion in response to said
20 reflective signal for obtaining said photic image signal having said plurality of basic image signals.

3. A photic image processing method as claimed in Claim 2, where further includes a step of:

(1c) executing a current amplification for said photic image signal in
25 order to enhance an anti-disturbance ability of said photic image signal.

4. A photic image processing method as claimed in Claim 1, wherein said step (2) further includes steps of:

(2a) eliminating a common-mode voltage of said photic image signal;

(2b) regulating a DC voltage offset of said photic image signal;

5 (2c) amplifying and outputting said photic image signal whose said DC voltage offset is regulated; and

(2d) performing said first regulating compensation in response to a control signal, in order to equilibrate said basic image signals of said photic image signal.

10 5. A photic image processing method as claimed in Claim 4, wherein said basic image signals of said photic image signal are respectively 3 basic signals indicative of red, green and blue fundamental colors.

6. A photic image processing method as claimed in Claim 5, where is executed by a photic image pick-up circuit including a lamp having a brightness, a lens and charge coupled device (CCD).

15 7. A photic image processing method as claimed in Claim 6, wherein said first regulating compensation regulates and equilibrates said photic image signals of red, green and blue fundamental colors and compensates a lamp aging phenomenon of said photic image pick-up circuit.

20 8. A photic image processing method as claimed in Claim 5, wherein said step (3) further includes steps of:

(3a) equally dividing said period of time into three segments, and multiplexing said 3 basic signals of red, green and blue fundamental colors in said three segments to obtain a multiplexed photic image signal alternately containing therein said 3 basic signals;

(3b) outputting three compensation values at said three segments, each of said three compensation values compensating one of said 3 basic signals of red, green and blue fundamental colors at the corresponding segment in said multiplexed photic image signal; and

5 (3c) compensating said 3 basic signals of red, green and blue fundamental colors in said multiplexed photic image signal by multiplying respectively said three compensation values therefor to accomplish said second regulating compensation.

9. A photic image processing device as claimed in Claim 6, wherein
10 said second regulating compensation correlates and compensates a non-uniformity among said lamp's brightness, said lens, and said charge coupled device (CCD).

10. A photic image processing method according to claim 8, wherein said method further includes steps of:

15 (5) converting said second compensated multiplexed photic image signal into a digital photic image signal; and

(6) generating said control signal corresponding to said digital photic image signal.

11. A photic image processing method comprising steps of:

20 (1) processing a photic image unit to generate a photic image signal having a plurality of basic image signals;

(2) performing a first regulating compensation to each of said basic
image signals of said photic image to generate a first compensated basic
image signals in order to equilibrate said basic image signals of said
25 photic image signal;

(3) multiplexing said first compensated basic image signals in a period of time to generate a multiplexed photic image signal having said

compensated basic image signals in series in said period of time, wherein said period is equal to a time of processing a photic image unit ; and

- (4) performing a second regulating compensation for said multiplexed photic image signal to generate a second compensated multiplexed photic image signal;

(5) converting said second compensated multiplexed photic image signal into a digital photic image signal; and

(6) generating a control signal;

wherein said step (2) further includes steps of:

- (2a) eliminating a common-mode voltage of said photic image signal;
- (2b) regulating a DC voltage offset of said photic image signal;
- (2c) amplifying and outputting said photic image signal whose said DC voltage offset is regulated; and
- (2d) performing said first regulating compensation in response to a control signal, in order to equilibrate said basic image signals of said photic image signal.

12. A photic image processing method comprising steps of:

(1) processing a photic image unit to generate a photic image signal having a plurality of basic image signals;

- (2) performing a first regulating compensation to each of said basic image signals of said photic image to generate a first compensated basic image signals in order to equilibrate said basic image signals of said photic image signal;

(3) multiplexing said first compensated basic image signals in a period of time to generate a multiplexed photic image signal having said compensated basic image signals in series in said period of time, wherein said period is equal to a time of processing a photic image unit ;

(4) performing a second regulating compensation for said multiplexed photic image signal to generate a second compensated multiplexed photic image signal;

wherein said basic image signals of said photic image signal are
5 respectively 3 basic signals indicative of red, green and blue fundamental colors, where is executed by a photic image pick-up circuit including a lamp having a brightness, a lens and charge coupled device (CCD), and wherein said first regulating compensation regulates and equilibrates said photic image signals of red, green and blue fundamental colors and
10 compensates a lamp aging phenomenon of said photic image pick-up circuit.

13. A photic image processing method as claimed in Claim 12, wherein said step (3) further includes steps of:

(3a) equally dividing said period of time into three segments, and
15 multiplexing said 3 basic signals of red, green and blue fundamental colors in said three segments to obtain a multiplexed photic image signal alternately containing therein said 3 basic signals;

(3b) outputting three compensation values at said three segments, each of said three compensation values compensating one of said 3 basic
20 signals of red, green and blue fundamental colors at the corresponding segment in said multiplexed photic image signal; and

(3c) compensating said 3 basic signals of red, green and blue fundamental colors in said multiplexed photic image signal by multiplying respectively said three compensation values therefor to
25 accomplish said second regulating compensation.

14. A photic image processing device as claimed in Claim 13, wherein said second regulating compensation correlates and compensates a non-

uniformity among said lamp's brightness, said lens, and said charge coupled device (CCD).

[illegible]

PHOTIC IMAGE PROCESSING DEVICE

ABSTRACT OF THE DISCLOSURE

The present invention relates to a photic image processing method which includes steps of (1) processing a photic image unit to generate a
5 photic image signal having a plurality of basic image signals, (2)
performing a first regulating compensation to each of the basic image
signals of the photic image to generate a first compensated basic image
signals in order to equilibrate the basic image signals of the photic image
signal, (3) multiplexing the first compensated basic image signals in a
10 period of time to generate a multiplexed photic image signal having the
compensated basic image signals in series in the period of time, wherein
the period is equal to a time of processing a photic image unit , and (4)
performing a second regulating compensation for the multiplexed photic
image signal to generate a second compensated multiplexed photic
15 image signal. The photic image processing method disclosed in this
disclosure is capable of producing a photic image having high resolution
and quality.




Fig. 1




Fig. 2

Declaration and Power of Attorney For Patent Application

English Language Declaration

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

PHOTIC IMAGE PROCESSING METHOD

the specification of which

(check one)

☒ is attached hereto.

☐ was filed on _____ as
Application Serial No. _____
and was amended on _____

(if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, § 1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, § 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)			Priority Claimed	
<u>85203068</u>	<u>Taiwan</u>	<u>27/2/1996</u>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
(Number)	(Country)	(Day/Month/Year Filed)	Yes	No
<u> </u>	<u> </u>	<u> </u>	<input type="checkbox"/>	<input type="checkbox"/>
(Number)	(Country)	(Day/Month/Year Filed)	Yes	No
<u> </u>	<u> </u>	<u> </u>	<input type="checkbox"/>	<input type="checkbox"/>
(Number)	(Country)	(Day/Month/Year Filed)	Yes	No

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of title 35, United States Code, § 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, § 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Serial No.)

(Filing Date)

(Status)

(patented, pending, abandoned)

(Application Serial No.)

(Filing Date)

(Status)

(patented, pending, abandoned)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

POWER OF ATTORNEY: I hereby appoint the registrants of Knobbe, Martens, Olson & Bear, LLP, 620 Newport Center Drive, Sixteenth Floor, Newport Beach, California 92660, Telephone (949) 760-0404, Customer No. 20,995

Send Correspondence to Knobbe, Martens, Olson & Bear, LLP
620 Newport Center Drive, Sixteenth Floor, Newport Beach, California 92660
Direct Telephone Calls to: Knobbe, Martens, Olson & Bear, LLP
at telephone No. (949) 760-0404

Full name of sole or first inventor	
Peen-Pau Cheng	
Inventor's signature	Date
Peen-Pau Cheng 12/15/99	December 15, 1999
Residence	
No. 25, R&D Rd. 2, Science-Based Industrial Park, Hsinchu 300, Taiwan, R.O.C	
Citizenship	
A citizen of Taiwan, R.O.C.	
Post Office Address	
The same as above	
Full name of second joint inventor, if any	
Second Inventor's signature	Date
Residence	
Citizenship	
Post Office Address	

(Supply similar information and signature for third and subsequent joint inventors.)

SUPPLEMENTAL OATH - USA PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name;

I believe I am an original, first and joint inventor of the subject matter which is claimed and for which a patent is sought on the invention entitled PHOTIC IMAGE PROCESSING DEVICE the specification of which is attached hereto;

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above;

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56;

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s) listed below, and insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code § 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56, which became available between the filing date of the prior application and the national or PCT international filing date of this application:

Priority claimed?

Number	Country	Date Filed	Yes	No
(1) 08/739,179	U.S.A.	10/30/1996	X	

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)

Priority claimed?

Number	Country	Date Filed	Yes	No
(1) 85203068	Taiwan	2/27/1996		X

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful, false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of first inventor: **Peen-Pau Cheng**

Inventor's signature Peen-Pau Cheng

Date 1/27/2000

Residence: **No. 25 R & D Rd 2, Science-Based Industrial Park, Hsinchu 300, Taiwan R.O.C.**

Citizenship: **Taiwan**

Send Correspondence To:

KNOBBE, MARTENS, OLSON & BEAR, LLP

Customer No. 20,995

H:\DOCS\LOAN\LOA-3607 DOC\010700

20000127